

PETERS

AMMUNITION RETAIL PRICE LIST



with
**RUSTLESS
PRIMING**

**SHOTGUN SHELLS, PISTOL
REVOLVER AND RIFLE CARTRIDGES**

including 11% U. S. Excise Tax
EFFECTIVE JANUARY 5, 1959
(Subject to change without notice)

FAIR TRADE

The retail prices shown herein on loaded shotgun shells and loaded metallic cartridges have been established as minimum Fair Trade prices in all states having Fair Trade laws in effect. This price list constitutes the notice provided for in all Peters Fair Trade agreements.

PETERS "HIGH VELOCITY" SHOTGUN SHELLS

Index No.	Gauge	Length Shell Inches	Powder Equiv. Drams	Ozs. Shot	Standard Shot Size	Retail Per Box Zones 1-2-3-4
100	10 Ga.	2 ⁷ / ₈	4 ³ / ₄	1 ⁵ / ₈	BB, 2, 4,	4.15
120	12 Ga.	2 ³ / ₄	3 ³ / ₄	1 ¹ / ₄	BB, 2, 4, 5, 6, 7 ¹ / ₂	3.40
†† 150	16 Ga.	2 ⁹ / ₁₆	3	1 ¹ / ₈	2, 4, 5, 6, 7 ¹ / ₂	3.10
160	16 Ga.	2 ³ / ₄	3	1 ¹ / ₈	2, 4, 5, 6, 7 ¹ / ₂	3.10
170	16 Ga.	2 ³ / ₄	3 ¹ / ₄	1 ¹ / ₈	2, 4, 5, 6, 7 ¹ / ₂	3.15
200	20 Ga.	2 ³ / ₄	2 ³ / ₄	1	2, 4, 5, 6, 7 ¹ / ₂	2.95
280	28 Ga.	2 ³ / ₄	2 ¹ / ₄	³ / ₄	4, 6, 7 ¹ / ₂ , 9*	3.05
4190	410 Ga.	2 ¹ / ₂	¹ / ₂	4, 5, 6, 7 ¹ / ₂ , 9*	2.30
4130	410 Ga.	3	³ / ₄	4, 5, 6, 7 ¹ / ₂ , 9*	2.65

PETERS "VICTOR" SHOTGUN SHELLS

Index No.	Gauge	Length Shell Inches	Powder Equiv. Drams	Ozs. Shot	Standard Shot Size	Retail Per Box Zones 1-2-3-4
5110	12 Ga.	2 ³ / ₄	3	1	4, 5, 6, 8	2.65
5140	12 Ga.	2 ³ / ₄	3	1 ¹ / ₈	4, 5, 6, 8, 9	2.80
5160	12 Ga.	2 ³ / ₄	3 ¹ / ₄	1 ¹ / ₈	4, 5, 6, 8	2.85
7170	12 Ga.	2 ³ / ₄	3 ¹ / ₄	1 ¹ / ₄	7 ¹ / ₂ , 8	3.00
†† 5530	16 Ga.	2 ⁹ / ₁₆	2 ¹ / ₂	1	4, 5, 6, 8, 9	2.50
5560	16 Ga.	2 ³ / ₄	2 ³ / ₄	1 ¹ / ₈	4, 6, 8	2.65
5730	20 Ga.	2 ³ / ₄	2 ¹ / ₄	⁷ / ₈	4, 5, 6, 8, 9	2.40
5740	20 Ga.	2 ³ / ₄	2 ¹ / ₂	1	4, 6, 8	2.55

PETERS "HIGH VELOCITY" MAGNUM LOADS

† RX10 Mag	10 Ga.	3 ¹ / ₂	5	2	BB, 2, 4, mag.	7.05
130S Mag	12 Ga.	2 ³ / ₄	4	2 ¹ / ₂	2, 4, 6, mag.	3.90
9170 Mag	12 Ga.	3	4 ¹ / ₂	1 ⁵ / ₈	BB, 2, 4, 5, 6, mag.	4.25
140H Mag	12 Ga.	3	4 ¹ / ₂	1 ⁷ / ₈	BB, 2, 4, mag.	4.60
180S Mag	16 Ga.	2 ³ / ₄	3 ¹ / ₂	1 ¹ / ₄	2, 4, 6, mag.	3.40
190S Mag	20 Ga.	2 ³ / ₄	3	1 ¹ / ₈	2, 4, 6, 7 ¹ / ₂ mag.	3.10

PETERS "VICTOR" SPREADER LOADS

6140SPDR	12 Ga.	2 ³ / ₄	3	1 ¹ / ₈	8	2.95
6540SPDR	16 Ga.	2 ⁹ / ₁₆	2 ¹ / ₂	1	8	2.65
6730SPDR	20 Ga.	2 ¹ / ₂	2 ¹ / ₄	⁷ / ₈	8	2.50

PETERS "HIGH VELOCITY" RIFLED SLUG LOADS

120RS	12 Ga.	2 ³ / ₄	3 ³ / ₄	1	Rifled Slug	5.10
160RS	16 Ga.	2 ⁹ / ₁₆	3	⁷ / ₈	Rifled Slug	4.85
200RS	20 Ga.	2 ¹ / ₂	2 ³ / ₄	⁵ / ₈	Rifled Slug	4.65

PETERS "VICTOR" TARGET LOADS

* 7160	12 Ga.	2 ³ / ₄	3	1 ¹ / ₈	7 ¹ / ₂ , 8, 9	2.80
--------	--------	-------------------------------	---	-------------------------------	--	------

* Maximum load for Registered Shoots is 3drs. 1¹/₈ oz. shot.

280RS	28 Ga.	2¼	2¼	½	Rifled Slug	4.75
410RS	410 Ga.	2½	Rifled Slug	4.35

PETERS "HIGH VELOCITY" BUCKSHOT LOADS

X340	12 Ga.	2¾	3¾	0	Buck-12 Pellets	4.10
X3400	12 Ga.	2¾	3¾	00	Buck- 9 Pellets	4.10
X341	12 Ga.	2¾	3¾	1	Buck-16 Pellets	4.10
X344	12 Ga.	2¾	3¾	4	Buck-27 Pellets	4.10
X351	16 Ga.	2 ⁹ / ₁₆	3	1	Buck-12 Pellets	4.10
X363	20 Ga.	2½	2¾	3	Buck-20 Pellets	4.10

Shot sizes underscored supplied only in rolled crimp.

* 410 Ga. and 28 Ga. with No. 9 Shot are marked "Target Load" and are known as Load Numbers 289, 7199 and 7139.

7129	12 Ga.	2¾	2¼	1	9	2.50
7539	16 Ga.	2¾	2¼	1	9	2.50
7739	20 Ga.	2¾	2¼	¾	9	2.40

PETERS "HIGH VELOCITY" TARGET LOADS

289	28 Ga.	2¾	2¼	¾	9	3.05
7199	410 Ga.	2½	½	9	2.30
7139	410 Ga.	3	¾	9	2.65

† Remington Express

†† Only for 16 gauge guns having 2⁹/₁₆" chambers.

All loaded shells packed 25 to a carton — 500 to the case.

PETERS RIM FIRE CARTRIDGES

**PETERS "HIGH VELOCITY" RUSTLESS
MAXIMUM POWER — HIGHEST SPEED**

Index No.		No. In Box	Retail Per Box Zones 1-2-3-4
2267	22 Short,	50	.55
2268	22 Short, H.P.	50	.66
2265	22 Short, Thunderbolt	28	.33
2269	22 Long,	50	.70
2283	22 Long Rifle,	50	.78
2284	22 Long Rifle, H.P.	50	.88
2291	22 W.R.F. (Rem. Spc.)	50	1.75

H.P.—Hollow Point

PETERS SPECIAL MATCH CARTRIDGES

2226	22 Long Rifle, Match, for Rifles	50	1.18
2228	22 Long Rifle, Match, for Pistols	50	1.18

**PETERS SHOT CARTRIDGE
RIM FIRE**

2299	22 Long Rifle, H.V.	50	1.31
------	--------------------------	----	------

PETERS STANDARD VELOCITY

Index No.		No. In Box	Retail Per Box Zones 1-2-3-4
2214	22 Short, "Target"	50	.55
2224	22 Long Rifle, "Target"	50	.78
2204	22 Short Gallery K.B.	250	2.75
2206	22 Short Gallery K.B.	50	.55
2205	22 Short Gallery Improved K.B.	250	2.75
2237	22 Win. Automatic	50	1.75
3203	32 Short	50	2.40
3206	32 Long	50	2.51

K.B.—Krumble Ball

PETERS BLANK CARTRIDGES

LOADED WITH A SPECIAL POWDER INSURING A LOUD REPORT

2249	22 Short	50	.68
3297	32 S & W	50	3.10
3894	38 S & W	50	3.20
3895	38 Special	50	4.40
3042	30-06 Spring., (Paper Bullet)	20	4.55

PETERS CARTRIDGE DIVISION

REMINGTON ARMS COMPANY, INC., BRIDGEPORT 2, CONNECTICUT
BRANCH WAREHOUSE — 3401 CHOUTEAU AVE., ST. LOUIS 3, MO.

PETERS CENTER FIRE CARTRIDGES

"RUSTLESS" PRIMING

Index No.	Size	Bullet		No. In Box	Retail Per Box	2801 7mm. Mau. 175 S.P. 20 4.55	3088 308 Win. 180 I.B. PT. S.P. HV 20 4.55	3102 8mm Mauser 170 I.B.S.P. 20 4.55	3853 380 Auto.* (9 mm.) 95 M.C. 50 4.50
		Wt. Grs.	Style						
†0218	218 Bee	46	Mush. H S	50	6.00	†0230 30(7.63mm) AP Mauser 85 M.C. O.P. 50 5.20	†8808 8mm Lebel 170 S.P. H S 20 5.15	3851 38 Auto.* (Reg. A) 130 M.C. 50 4.70	
†0219	219 Zipper	56	Mush. H S	20	3.45	3052 30 Luger* (7.65 mm.) 93 M.C. 50 5.20	3262 32 S & W* 88 Lead 50 3.30	3849 38 Super* Auto. (B) 130 M.C. 50 4.70	
†0822	220 Swift	48	S.P. H S	20	3.70	3064 30-30 Win 160 M.C. H V 20 3.60	3265 32 S & W,* Long 98 Lead 50 3.50	3822 38 S & W* 146 Lead 50 4.10	
2244	222 Rem.	50	S.P. H V	20	2.80	3043 30-30 Win 170 I.B.H.P. H V 20 3.60	3252 32 Short* Colt 80 Lead 50 3.25	3844 38 Special* 158 Lead 50 4.40	
†0922	222 Rem.	50	H.S. M.C.	20	2.80	3058 30-30 Win 170 I.B.S.P. H V 20 3.60	3254 32 Long* Colt 80 Lead 50 3.50	3841 38 Special* 200 Lead 50 4.60	
2246	222 Rem. Mag.	55	H.S. S.P.	20	3.10	3044 30-30 Win 150 I.B.S.P. H V 20 3.60	3256 32 Colt NP* 100 Lead 50 3.50	3826 38 Special* 158 Met. Pt. 50 5.20	
2274	22 Hornet	45	M.C.H.P. HV	50	6.00	3054 30 Rem. 170 I.B.S.P. H V 20 3.60	3260 32 Auto.* (7.65mm) 71 M.C. 50 4.40	3847 38 Special* 148 Lead PM WC 50 4.60	
2276	22 Hornet	45	S.P. H V	50	6.00	3047 30-40 Krag 220 I.B.S.P. H V 20 4.55	3269 32-20 Win.* 100 Lead 50 5.10	3842 38 Special* (38-44) 158 Lead H V 50 4.85	
2431	243 Win	80	PT. S.P. HV	20	4.10	3046 30-40 Krag 180 I.B.S.P. H V 20 4.55	3270 32-20 Win! 100 S.P. 50 6.30	3810 38 Special 110 Sp. MP H V 50 5.20	
2432	243 Win	100	I.B. PT. S.P. HV	20	4.10	3051 30-40 Krag 180 I.B. PT. S.P. HV 20 4.55	3272 32-20 Win. 80 M.C.H.P. HV 50 6.80	3831 38 Colt NP* 150 Lead 50 4.10	
2441	244 Rem	75	PT. S.P. HV	20	4.10	†6630 30-06 Spfd. 110 (3380 f.s.) HS PT.S.P. 20 4.55	3278 32 Win Spc 170 I.B.H.P. H V 20 3.70	3833 38 Short* Colt 125 Lead 50 3.75	
2442	244 Rem.	90	PT. S.P. H V	20	4.10	3033 30-06 Spfd 150 I.B. PT. S.P. HV 20 4.55	3279 32 Win Spc 170 I.B.S.P. H V 20 3.70	3835 38 Long* Colt 150 Lead 50 4.10	
2443	244 Rem.	90	P.P. Exp. H V	20	4.10	3036 30-06 Spfd 220 I.B.H.P. H V 20 4.55	3288 32-40 Win 165 S.P. 20 3.55	3856 38-40 Win.* 180 S.P. 50 6.80	
2552	25-20 Win	86	Lead	50	5.10	3038 30-06 Spfd 220 I.B.S.P. H V 20 4.55	3481 348 Win. 150 S.P. H V 20 5.40	3872 38-55 Win 255 S.P. 20 3.60	
2553	25-20 Win	86	S.P.	50	5.65	3039 30-06 Spfd 180 I.B. PT. S.P. HV 20 4.55	3484 348 Win. 200 I.B.S.P. H V 20 5.40	4154 41 Long* Colt 195 Lead 50 5.00	
2555	25-20 Win	60	M.C.H.P. HV	50	5.95	3077 30-06 Spfd 150 P.P. Exp. H V 20 4.55	3586 351 Win. S L 177 M.C. 50 7.35	4405 44 S & W Spc.* 246 Lead 50 5.90	
2562	25 (6.35 mm.) Auto *	50	M.C.	50	3.85	3080 30-06 Spfd 180 P.P. Exp. H V 20 4.55	3585 351 Win. S L 180 S.P. 50 7.35	4410 44 Rem. Mag.* 240 Lead 50 7.75	
†5425	257 Rob.	100	P T.S.P.C.L.	20	4.25	3056 30-06 Spfd 180 I.B.S.P. H V 20 4.55	3592 35 Rem 150 I.B. PT. S.P. HV 20 4.10	4409 44-40 Win.* 200 S.P. 50 7.10	
2584	257 Rob.	117	I.B.S.P. H V	20	4.25	3079 30-06 Spfd 180 Match T H 20 5.80	3594 35 Rem. 200 I.B.H.P. H V 20 4.10	4502 45 Colt * 250 Lead 50 5.90	
2582	25-35 Win	117	I.B.S.P. H V	20	3.55	3021 300 Savage 180 I.B.S.P. H V 20 4.40	3589 35 Rem. 200 I.B.S.P. H V 20 4.10	4504 45 Auto.* 230 M.C. 50 6.25	
2568	250 Savage	100	I.B.S.P. H V	20	3.85	3023 300 Savage 180 I.B. PT. S.P. HV 20 4.40	3575 357 Mag.* 158 Lead H V 50 5.20	4507 45 Auto.* 185 M.C. PM WC 50 6.50	
2570	250 Savage	100	I.B. PT. S.P. HV	20	3.85	3019 300 Savage 150 I.B.S.P. H V 20 4.40	†8835 357 Mag. 158 M.P. H S 50 5.95	4512 45 Auto.* 173 Spc. MP HV 50 6.80	
2572	250 Savage	87	S.P. H V	20	3.85	3024 300 Savage 150 I.B. PT. S.P. HV 20 4.40	3651 9 mm.* Luger 124 M.C. 50 5.75	4506 45 Auto.* Rim 230 Lead 50 5.75	
2701	270 Win.	100	I.B. PT. S.P. HV	20	4.55	3084 300 Savage 150 P.P. Exp. H V 20 4.40		4553 45-70 Gov't 405 S.P. 20 4.40	
2702	270 Win.	150	I.B.S.P. H V	20	4.55	3027 300 H & H 220 I.B.H.P. H V 20 5.75			
2704	270 Win.	130	P.P. Exp. H V	20	4.55	3028 300 H & H 180 I.B. PT. S.P. HV 20 5.75			
2705	270 Win.	130	I.B. PT. S.P. HV	20	4.55	†7730 300 H & H 180 Match T H 20 7.10			
2810	280 Rem.	125	I.B. PT. S.P. HV	20	4.55	3035 303 Savage 180 I.B.S.P. H V 20 3.70			
2811	280 Rem.	150	I.B. PT. S.P. HV	20	4.55	3085 303 British 215 S.P. 20 4.55			
2812	280 Rem.	165	I.B. S.P.	20	4.55	3086 308 Win. 110 I.B. PT. S.P. HV 20 4.55			
2813	280 Rem.	100	P.P. Exp. H V	20	4.55	3087 308 Win. 150 I.B. PT. S.P. HV 20 4.55			

PETERS CENTER FIRE SPORTING CARTRIDGE BASIC BALLISTICS

● rifle cartridges

Cartridge	Bullet		Muzzle Vel. F.P.S.	Muzzle Energy F. Lbs.	Mid-Range Traj. 100 Yds.	Cartridge	Bullet		Muzzle Vel. F.P.S.	Muzzle Energy F. Lbs.	Mid-Range Traj. 100 Yds.	Cartridge	Bullet		Muzzle Vel. F.P.S.	Muzzle Energy F. Lbs.	Mid-Range Traj. 100 Yds.
	Wt. Grs.	Style					Wt. Grs.	Style					Wt. Grs.	Style			
22 Hornet H.V.	45	M.C.H.P.	2690	720	0.8	30 Remington	160	M.C.	2220	1750	1.0	30-40 Krag H.V.	220	I.B.S.P.	2200	2360	1.0
22 Hornet H.V.	45	S.P.	2690	720	0.8	30 Remington H.V.	170	I.B.H.P.	2220	1860	1.2	30-40 Krag H.V.	220	I.B.S.P.	2200	2360	1.0
222 Remington H.V.	50	S.P.	1200	1140	0.5	30 Remington H.V.	170	I.B.S.P.	2220	1860	1.2	308 Winchester H.V.	110	I.B. PT. S.P.	3340	2730	0.5

222 Remington Mag. H.V.	55	S.P.	3300	1330	0.5	300 Savage H.V.	150	P.I. Exp.	2670	2370	0.7	308 Winchester H.V.	150	I.B. PT. S.P.	2860	2730	0.6
243 Winchester H.V.	80	PT. S.P.	3500	2280	0.4	300 Savage H.V.	150	I.B.S.P.	2670	2370	0.7	308 Winchester H.V.	180	I.B. PT. S.P.	2610	2720	0.8
243 Winchester H.V.	100	I.B. PT. S.P.	3070	2090	0.5	300 Savage H.V.	150	I.B. PT. S.P.	2670	2370	0.7	8 mm Mauser	170	I.B.S.P.	2570	2490	0.8
244 Remington H.V.	75	PT. S.P.	3500	2040	0.4	300 Savage H.V.	180	I.B.S.P.	2370	2240	0.9	32 Remington H.V.	170	I.B.S.P.	2220	1860	1.0
244 Remington H.V.	90	PT. S.P.	3200	2050	0.5	300 Savage H.V.	180	I.B. PT. S.P.	2370	2240	0.9	32 Remington H.V.	170	I.B.H.P.	2220	1860	1.0
244 Remington H.V.	90	P.P. Exp.	3200	2050	0.5	300 H.&H. Mag. H.V.	180	I.B. PT. S.P.	2920	3400	0.6	32 Win. Special H.V.	170	I.B.H.P.	2280	1960	1.0
250 Savage H.V.	87	S.P.	3030	1770	0.6	300 H.&H. Mag. H.V.	220	I.B.H.P.	2620	3350	0.7	32 Win. Special H.V.	170	I.B.S.P.	2280	1960	1.0
250 Savage H.V.	100	I.B.S.P.	2820	1760	0.6	30-06 Springfield	150	M.C.	2810	2630	0.6	32-20 Win. H.V.	80	M.C.H.P.	2100	780	1.5
250 Savage H.V.	100	I.B. PT. S.P.	2820	1760	0.6	30-06 Springfield H.V.	150	I.B. PT. S.P.	2970	2930	0.6	32-20 Win.	100	Lead	1290	370	3.3
25-20 Winchester H.V.	60	M.C.H.P.	2250	675	1.2	30-06 Springfield H.V.	150	P.P. Exp.	2970	2930	0.5	32-20 Win.	100	S.P.	1290	370	3.3
25-20 Winchester	86	Lead	1460	405	2.6	30-06 Springfield H.V.	180	I.B. PT. S.P.	2700	2910	0.7	32-40 Win.	165	S.P.	1440	760	2.4
25-20 Winchester	86	S.P.	1460	405	2.6	30-06 Springfield H.V.	180	I.B.S.P.	2700	2910	0.7	348 Win. H.V.	150	S.P.	2890	2780	0.6
25-35 Winchester	117	M.C.	2300	1370	1.0	30-06 Springfield H.V.	180	P.P. Exp.	2700	2910	0.7	348 Win. H.V.	200	I.B.H.P.	2530	2840	0.8
25-35 Winchester H.V.	117	I.B.S.P.	2300	1370	1.0	30-06 Springfield	180	Match H.V.	2700	2910	0.6	348 Win. H.V.	200	I.B.S.P.	2530	2840	0.8
257 Roberts H.V.	117	S.P.	2650	1820	0.7	30-06 Springfield H.V.	220	I.B.H.P.	2410	2830	0.8	35 Remington H.V.	150	I.B. PT. S.P.	2400	1920	0.9
270 Winchester H.V.	100	I.B. PT. S.P.	3480	2690	0.4	30-06 Springfield H.V.	220	I.B.S.P.	2410	2830	0.8	35 Remington H.V.	200	I.B.S.P.	2210	2170	1.1
270 Winchester H.V.	130	P.P. Exp.	3140	2840	0.5	303 Savage H.V.	180	I.B.H.P.	2140	1830	1.1	35 Remington H.V.	200	I.B.H.P.	2210	2170	1.1
270 Winchester H.V.	130	I.B. PT. S.P.	3140	2840	0.5	303 Savage H.V.	180	I.B.S.P.	2140	1830	1.1	351 Win. Self-Loading	177	M.C.	1850	1370	1.5
270 Winchester H.V.	150	I.B.S.P.	2800	2610	0.6	303 British	215	S.P.	2180	2270	1.1	351 Win. Self-Loading	180	S.P.	1850	1370	1.5
280 Remington H.V.	125	I.B. PT. S.P.	3140	2740	0.5	30-30 Winchester H.V.	150	I.B.S.P.	2410	1930	0.9	38-40 Win.	180	S.P.	1330	705	3.2
280 Remington H.V.	150	I.B. PT. S.P.	2810	2630	0.6	30-30 Winchester H.V.	170	I.B.H.P.	2220	1860	1.2	38-55 Win.	255	S.P.	1320	985	2.9
280 Remington H.V.	165	I.B. S.P.	2770	2810	0.7	30-30 Winchester H.V.	170	I.B.S.P.	2220	1860	1.2	44-40 Win.	200	S.P.	1310	760	3.3
280 Remington H.V.	100	P.P. Exp.	3570	2830	0.4	30-40 Krag H.V.	180	I.B.S.P.	2470	2440	0.8	45-70 Govt.	405	S.P.	1320	1570	2.9
7 mm Mauser	175	S.P.	2490	2410	0.8	30-40 Krag H.V.	180	I.B. PT. S.P.	2470	2440	0.8						

● pistol and revolver cartridges

Cartridge	Bullet		Muzzle Vel. F.P.S.	Muzzle Energy F. Lbs.	Mid-Range Traj. 50 Yds.	Cartridge	Bullet		Muzzle Vel. F.P.S.	Muzzle Energy F. Lbs.	Mid-Range Traj. 50 Yds.	Cartridge	Bullet		Muzzle Vel. F.P.S.	Muzzle Energy F. Lbs.	Mid-Range Traj. 50 Yds.
	Wt. Grs.	Style					Wt. Grs.	Style					Wt. Grs.	Style			
25 (6.35 mm) Automatic	50	M.C.	810	73	1.8	38 Smith & Wesson	146	Lead	730	173	2.2	38 Super Automatic	130	M.C.	1275	469	0.8
30 Luger (7.65 mm) Auto	93	M.C.	1220	307	0.9	38 Sp. Metal Penet'g H.V.	110	Special	1320	425	0.7	38 Automatic	130	M.C.	1040	312	1.0
32 Short Colt	80	Lead	795	112	1.9	38 Special Police Match	148	Lead W.C.	770	170	2.1	380 Automatic (9 mm)	95	M.C.	955	192	1.4
32 Long Colt	80	Lead	790	111	1.9	38 Special Police Match	158	Lead	855	256	1.6	41 Long Colt	195	Lead	730	231	2.2
32 Colt New Police	100	Lead	785	137	1.9	38 Special	158	Lead	855	256	1.6	44 Remington Magnum	240	Lead Gas Check	1570	1310	0.6
32 (7.65 mm) Auto	71	M.C.	960	145	1.3	38 Special Metal Point	158	M.P.	855	256	1.6	44 Smith & Wesson Spc.	246	Lead	755	311	2.0
32 Smith & Wesson	88	Lead	705	97	2.6	38 Special H.V.	158	Lead	1085	413	1.0	45 Colt	250	Lead	855	405	1.6
32 Smith & Wesson Long	98	Lead	780	132	1.9	38 Special	200	Lead	730	236	2.2	45 Auto Met. Penet'g H.V.	173	Special	1125	486	1.0
32 S.&W. Long Pol. Match	98	Lead W.C.	780	132	2.3	38 Colt New Police	150	Lead	680	154	2.5	45 Auto Police Match	185	M.C.W.C.	875	314	1.6
357 Magnum H.V.	158	Lead	1430	717	0.6	38 Short Colt	125	Lead	760	160	2.1	45 Automatic	230	M.C.	850	369	1.6
9 mm Luger Auto	124	M.C.	1120	345	1.0	38 Long Colt	150	Lead	770	197	1.9	45 Automatic Rim	230	Lead	805	331	1.8

Reg. A—Adapted for Colt Military and Pocket Model Automatic Arms
 B—Adapted for Colt Super Automatic Arms
 S.P.—Soft Point
 M.C.—Metal Case
 I.B.S.P.—Inner Belted Soft Point
 I.B.H.P.—Inner Belted Hollow Point
 O.P.—Oil Proof
 P.P. Exp.—Protected Point Expanding
 H.S.—Hi-Speed
 PT.—Pointed
 C.L.—Core-Lokt
 * "Oil-Tite"
 H.V.—High Velocity
 † Remington Brand
 M.C.H.P.—Metal Case Hollow Point
 T.H.—Taper Heel
 PT. S.P.—Pointed Soft Point
 W.C.—Wad Cutter
 P.M.—Police Match
 MET.PT.—Metal Point
 Spc.—Special
 M.P.—Metal Penetrating
 H.P.—Hollow Point
 N.P.—New Police

"Victor," "Target," "Krumble Ball" and "Thunderbolt" are Reg. U.S. Pat. Off. and "High Velocity," "Highway Patrol," "Inner Belted," "Police Match," "Rustless" are trade-marks of Peters Cartridge Division, "Core-Lokt" is Reg. U.S. Pat. Off. and "Hi-Speed" is a trade-mark of Remington Arms Company, Inc., Bridgeport 2, Conn.